

Product Code: CSP010

Description: Smart Gateway Hub



General Information

Dimensions	90mm (L) x 90mm (W) x 23mm (D)	
Materials	Housing: Polycarbonate	Electronics: PCB & Electronic Components
Working Voltage	1.8-3.3V	
Protocol	Zigbee	
Working Humidity	10%-90%RH (Non-condensing)	
Wireless Technology	WIFI 801.11 b/g/n	
System Requirements	Mobile Device Running IOS 8 or Higher or Android 4.1x or Higher.	
Ingress Protection	IP20	
Operational Temperature	-10°C to +55°C	
Warranty	1 Year	
Standards	BS EN 60950-1 BS EN 55035 BS EN 61000-3-2: 2014 BS EN 61000-3-3 : 2013 A1: 2019 BS EN 62311: 2008	

Additional Information

Required for controlling Zigbee devices via the app and voice control
 Overview of how many devices can be connected:

- Hardwired Connected Devices Only: 256
- Battery Powered Devices Only (With x1 Hub): 32
- Mix of Both Battery Powered and Hardwired: 256 with a Maximum of 62 Battery Powered Devices

NOTE: If you are pairing more than 128 devices within the range, please contact technical support on +44 (0) 1827 63454

Programming Information

Once paired to the app all Zigbee devices and voice control can be added.

