

Product Code: CSP031

Description: Smart Window & Door Sensor



General Information

Dimensions (Transmitter)	40mm (L) x 25mm (W) x 14.5mm (D)	
Dimensions (Magnet)	26mm (L) x 10mm (W) x 9mm (D)	
Materials	Housing: Polycarbonate	Electronics: PCB & Electronic Components
Working Voltage	3V DC	
Working Current	5mA (Average)	
Battery Type	CR 2032 (Supplied)	
Battery Lifetime	1 Year (Dependent On Use)	
Protocol	Zigbee	
Activation Distance	10mm-20mm (Between Sensor & Magnet)	
Standby Current	>3 uA	
Working Humidity	0%-95%RH (Non-condensing)	
Ingress Protection	IP20	
Operational Temperature	-10°C to +50°C	
Warranty	1 Year	
Standards	BS EN 60950-1 BS EN 55035 BS EN 61000-3-2: 2014 BS EN 61000-3-3 : 2013 A1: 2019 BS EN 62311: 2008	

Additional Information Control linked receivers through the ClickSmart+ app
Send activation alerts to your phone

Installation Overview Suitable for doors or windows.
Self-adhesive pads applied ready for installation.

Programming Information With hub and app setup with sensor having battery installed, using the pin supplied press the reset button for five seconds and the sensor LED will start flashing. Can be paired with hub via app.

